

DS-2CC502/512/592P(N)-FB

Vandal-proof Dome Camera



Key Features

- Compact design
- 1/3" Sony CCD
- Day / night auto swith
- Low illumination
- Auto white balance,auto gain control,electronic shutter control and backlight compensation
- Internal synchronization

Specifications

	DS-2CC502P(N)-FB	DS-2CC512P(N)-FB	DS-2CC592P(N)-FB
Camera			
Image sensor	1/3" Sony CCD		
Signal system	PAL / NTSC		
Effective pixels	PAL: 500 (H) × 582 (V) NTSC: 510 (H) × 492 (V)	PAL: 752 (H) × 582 (V) NTSC: 768 (H) × 494 (V)	PAL: 752 (H) × 582 (V) NTSC: 768 (H) × 494 (V)
Min. illumination	0.1 lux@F1.2, AGC on 0.18 lux@F1.6, AGC on		
Shutter time	PAL: 1/50s ~ 1/100,000s NTSC: 1/60s ~ 1/100,000s		
Lens	4 ~ 9 mm @F1.6 Angle of view: 74.6° ~ 32°		
Lens mount	Φ 14		
Angle adjustment	Pan: 0 ~ 355°; tilt: 0 ~ 90°;		
Day & night	Electronic		
Horizontal resolution	420 TVL	480 TVL	540 TVL
Synchronization	Internal synchronization		
Video output	1Vp-p composite output (75 Ω / BNC)		
S/N ratio	More than 48dB		
BLC	On		
General			
Operating conditions	-10°C ~ 60°C (14°F ~ 140°F) Humidity 90% or less (non-condensing)		
Power supply	12 VDC ± 10%		
Power consumption	2W max.		
Impact protection	IEC 60068-2-75 test, Eh, 50J; EN 50102, up to IK10.		
Dimensions	Φ 145 × 92 mm (Φ 5.71" × 3.62")		
Weight	660g (1.46 lbs)		

Available models

DS-2CC502P-FB, DS-2CC502N-FB, DS-2CC512P-FB, DS-2CC512N-FB, DS-2CC592P-FB, DS-2CC592N-FB

Dimensions

