

# CP-KAC-DY42L2

## Normal IR Dome Camera - 20 Mtr

### Main Features



- ⇒ 1/3" Sony Super HAD II CCD
- ⇒ 420 TVL Standard Resolution Camera
- ⇒ 0 lux @ F1.2 (IR ON)
- ⇒ 3.6 mm Fixed Lens
- ⇒ IR Range of 20 Mtrs with 24 LED's
- ⇒ AGC, AWB, BLC
- ⇒ CE, FCC and RoHS Certified



Feature	Specification
Image Sensor	1/3" Sony Super HAD II CCD
Pixels	PAL:537Hx597V, NTSC:537Hx505V
Resolution	420TVL
Min. Illumination	0 lux @ F1.2 (IR ON)
S/N Ratio	more than 48dB
Electronic Shutter	1/50(1/60) - 1/100000 Sec
Flickerless Mode	Yes
Gamma Correction	0.45
White Balance (AWB)	Auto
Gain Control (AGC)	Auto
Back Light Compensation	Auto
IR	24 LEDs, Upto 20 Mtrs
Sync	Internal
Video Output	1.0 Vp-p/75 ohm
Power Supply	DC 12V ± 5%
Power Consumption	<5W
Dimensions	93(Ø)×80(H)mm
Weight	160g
Operating Temperature	-10~50 °C
Certifications	CE, FCC, RoHS