

● IFACE 101 - Standalone Face+RFID Time and attendance Terminal

Product Description

IFace 101 multi-biometric identification time attendance terminal adopts latest Face 7.0 algorithm and large capacity memory .I Face series integrated 630MHz high speed Multi-Bio processor and high definition infrared camera enables user identification in the dark environment. Face and fingerprint multi-biometric identification method will be applicable more widely. All operations of I Face are designed to be performed on the 2.0 inches TFT screen with keypad operation. Multi-model communications includes RS232/485, TCP/IP, optional Wi-Fi or GPRS. Optional built-in 2000 mAh battery eliminates the trouble of power-failure



Technical Specification

- Dimension(WxHxD): 193.6 X 147.6 X 101 cm
- Face Capacity: 400 (1:N) /700(1:G) ,1500/3000(1:1) optional
- ID Card Capacity: 10,000
- Transaction Storage : 1,00,000
- Camera : High Resolution Infrared Camera
- Communications: RS232 ,RS485, TCP/IP ,USB
- Processor: Multi-Bio CPU 630 MHz
- Identification time : < =2S
- FAR: <=0.0001%
- FRR: <=1% Operating
- Temperature : 0°C - 45°C
- Operating Humidity : 20%-80%
- Power Supply: 12V DC ,3A
- Optional Function: Mifare Card ,Short MAssage ,WebServer ,WiFi ,GPRS ,9 Digit User ,Work Code
- Algorithm Version: Face 7.0
- Display : 2.0 Inch TFT Screen
- Gross Weight : 1.5 Kg