


DS-7304HFI-SE

Standalone DVR



DS-7304HFI-SE



Key features

- H.264 video compression
- 4CIF resolution real-time recording
- VGA output at up to 1280×1024 resolution
- Dual-stream
- 4-ch synchronous playback
- SMTP, NTP, SADP (IP Finder), DHCP protocols

Specifications

	DS-7304HFI-SE
Video / Audio input	
Video compression	H.264
Analog video input	4-ch
Video input interface	BNC connector (1.0 Vp-p, 75 Ω); PAL / NTSC self-adaptive
Audio compression	G.711
Audio input	4-ch, RCA connector (2.0 Vp-p, 1 kΩ)
Voice talk input	1-ch, RCA (2.0 Vp-p, 1 kΩ)
Video / Audio output	
VGA output	1-ch, resolution: 1280 × 1024 / 60 Hz, 1024 × 768 / 60 Hz
CVBS output	2-ch, BNC connector (1.0 Vp-p, 75 Ω); Resolution: PAL: 704 × 576, NTSC: 704 × 480
Audio output	1-ch, RCA connector (linear, 1 kΩ)
Recording resolution	4CIF / 2CIF / CIF
Frame rate	Main stream: 4CIF / 2CIF / CIF @ 25 fps (P) / 30 fps (N) Sub stream: CIF / QCIF
Video bit rate	32 kbps ~ 2048 kbps, or user defined (max. 3072 kbps)
Stream type	Video, Video & Audio
Audio bit rate	64 kbps
Dual-stream	Support
Synchronous playback	4-ch
Hard disk	
SATA	1 SATA interface
Capacity	Up to 2TB capacity for each disk
External interface	
Network interface	1, RJ45 10M / 100M self-adaptive ethernet interface
Serial interface	1 RS-485 full-duplex interface, 1 RS-232 interface
USB interface	2, USB 2.0
Alarm in	4
Alarm out	1
General	
Power supply	12 VDC
Consumption	≤ 10W (without hard disk or DVD-R/W)
Working temperature	-10 °C ~ +55 °C
Working humidity	10% ~ 90%
Chassis	Stand-alone 1U chassis
Dimensions (W x D x H)	315 × 230 × 45 mm
Weight	≤ 2kg (without hard disk or DVD-R/W)