

# SEC - SLE 07C AC FMC



## FEATURES

- 7" Colour TFT LCD display
- Slimline Series - Slim & Sleek Design
- Hands Free Operation
- Micro Controller Based with digital circuit
- Can connect up to 4 monitors (1 main monitor and 3 sub-monitors)
- Can connect 2 cameras
- Can connect with surface mount or flush mount camera
- External CCTV camera can be connected if using one VDP outdoor camera
- Exceptional audio clarity & volume
- Inbuilt Security Alarm
- TV output to see parallel image on TV screen
- Can attach optional RF receiver for remote operation (optional, separate for each monitor)
- Inbuilt Switch Mode Power Supply (SMPS)
- RS 485 connectivity between monitors, cameras and modules
- Monitor Function
- Door Lock Control
- 10 Amp relay with normally open (NO) and normally closed (NC) contacts for different types of locks
- Lock can be connected from outdoor camera and lock control module
- Alarm out - can connect to intruder alarm or auto dialer
- Tamper spring in camera with tamper alarm
- White LEDs for night vision
- Low power consumption
- Includes 1 Monitor and 1 Outdoor Flush Mount Camera

## TECHNICAL SPECIFICATIONS

<b>Indoor Monitor</b>	
Model	SEC - SLE 07C AC FMC
Display	7" Colour TFT LCD
Power Supply	Internal, SMPS +15V (0.8A), 5V (0.18A)
Power Consumption	16W Max
AC Input	220V/50Hz,
Input Range	140 - 260V AC
Communication	Hands Free Half Duplex
Button Functions	Monitor 1 , 2, Talk, Lock, Alarm, Display Settings and Volume
Mount type	Surface Mount
Mounting Bracket	Included
Maximum wire length from camera to last monitor	100m
TFT Resolution	1440 (H) x 234 (V) DOT
Wiring to Camera	1 Coaxial + 4
Wiring to Sub Monitor	1 Coaxial + 3
Connectors	Terminal Block
Lock Connection Source	Connection from Outdoor Camera & External Lock Control Module
Bell Sound	Ding Dong
Security Alarm Sound	Continuous Ding Dong in Monitor & Police Siren in Camera
Operating Temperature	5 °C to 60 °C
Dimensions (max.)	227mm (H) X 178mm (W) X 26mm (D)
Net Weight	705 gm
<b>Outdoor Flush Mount Camera</b>	
Power Supply	From indoor monitor
Power Consumption	2.75W Max
Camera	Flush Mount: CCD 1/3" 420TVL (Adjustable Camera Angle)
Minimum Illumination	0.1 Lux F2.0
Lens	3.6mm F2.0
Night Vision	White LED's with 1mtr visibility
Connectors	Flush Mount: Screw Type
Mount Type	Flush Mount: Partially Flush
Mounting Bracket	Flush Mount: N/A
Operating Temperature	5 °C to 60 °C
Siren Sound	Police Siren
Lock Type	NO / NC Type Electronic, Strike, Release, Electromagnetic, Others
Lock Power Supply	External, Not Included
Bell Sound	Ding Dong
Dimensions (max.)	Flush Mount: 125mm (H) X 100mm (W) X 66mm (D)
Weight	Flush Mount: 255 gm